



# K&W Tech Grade Knock'er Loose Lubricant Penetrant

## ATTRIBUTES –

### Product Description

A super-fast penetrant that attacks corrosion to free rusted & corroded fasteners & components. Powerful, concentrated formula penetrates & leaves behind a long-lasting lubricant that will prevent future corrosion.



### Applications

Rusted and frozen metals, such as bolts, hinges, nuts, hinges, exhaust clamps.

Net Fill	18 Wt Oz
Unit Dimensions	9.19H x 3W x 3D in
Appearance	Light Amber Liquid
Base Type	Petroleum Distillate
Flash point (F)	141°F
Flash point (C)	60.6°C
Flammability Class -	CPSC Flammable
Spec Gravity Concentrate	0.82
KB Value	28
Plastic Safe	OK
Safe on Most Plastics	(test small area)
Film Type	Thin, Non-Drying
Evaporation Rate	Slow
Dielectric Strength	6000Volts
Propellant	Carbon Dioxide
Aerosol Flammability	Level III
4 Ball EP	Not Determined
4 Ball Wear	Not Determined
Drop Point N/A	
Working Temp (F)	Max 300°F
Working Temp (C)	Max 148.9°C
VOC % (Consumer Product def)	24.1
VOC g/L (Consumer Product def)	197.6
VOC lb/gal (Consumer Prod def)	1.65
VOC Category	Penetrant
Removal (How To)	Remove with mineral spirits or degreasers etc.

**Distributed by:**

[orderus@evasausa.com](mailto:orderus@evasausa.com)

6701 NW 7TH ST  
MIAMI, FL 33126

